

EXTRACTO FOAM PLUS



INJECTION EXTRACTION WASHING WITH ACTIVE FOAM.

TECHNICAL SPECIFICATIONS

POWER	220/230V 50/60Hz
INJECTION WATER TANK	10 lt
STEM VOLUME	20 lt
DETERGENT FOAM TANK	5 lt
STRUCTURE	Acciaio e inox
WEIGHT	25 kg
SIZE	57x45xh105cm
ACTIVE FOAM BRUSH	✓ Tutte le versioni
SOLIDS AND LIQUIDS EXTRACTION	✓ Tutte le versioni
COLD WATER INJECTION AND EXTRACTION	Versioni BF429B e BF429C
HOT WATER INJECTION AND EXTRACTION	Versione BF429C
WATER INJECTION PRESSURE	7 bar
WATER INJECTION TEMPERATURE	50/60°C
WATER HEATER POWER	1850 W
SUCTION POWER	Motore bistadio 1400 W
SUCTION CAPACITY	60 lt/s - 215 m3/h



LIQUID AND
SOLID SUCTION



ACTIVE FOAM
FOR CLEANING



INJECTION/EXTRACTION
WITH HOT/COLD WATER
OR DETERGENT



HOT/COL
WATER

AVAILABLE VERSIONS:

BF429A Active foam and suction

BF429B Active foam, suction and water injection

BF429C Active foam, suction, injection of cold water and hot water

OPTIONAL ACCESSORIES



RIP6002
14W led lamp for
car interiors



BF360
Ozone generator
for sanitization



RIP1484
Detergent foam



OPTIONAL



CARFON BF350
Professional air dryer
for car interiors

EFFICIENCY, SAFETY and NOTES

- ✓ **RELIABILITY AND SAFETY** are guaranteed by a **COPPER BOILER**. Copper is an explosion-proof and antiscaling material. The **HEATERS** are placed externally, so they **NEVER** come into contact with water.
- ✓ 1 KW power creates a steam flow equal to 1,2 kg/h (20 g/min). The efficiency of steam is proportional to its flow, not to its pressure. There is no point in having high pressure and a low flow.
- ✓ The whole production is based in Italy, in our plant in Pesaro.

SPARE PARTS AND SERVICE

- ✂ **BIEFFE** guarantees the shipping of spare parts, accessories in very short times. Our efficient help line is available for service and assistance.
- ✉ For spare parts and service: info@bieffeitalia.it
- ➔ Visit our website: www.bieffeitalia.it

